

# SOUTHWEST RESEARCH INSTITUTE®

## Fuels and Lubricants Research Division

### JASO M340-18 Lubricity Test

#### Specifications

- JASO
- ISO 13738

#### Objective


- Evaluate the lubricity of a lubricant used in two-stroke cycle engines.

#### Field Service Simulated

- Two-stroke cycle gasoline engine operation such as motorcycle, utility, and outboard engines.

#### Test Fixture

- A Honda AF-27, type SK-50MM, air-cooled, single-cylinder, two-stroke cycle, spark-ignition engine is coupled to a high-speed 10-hp dynamometer.
- External cooling air is supplied to the engine by a variable delivery fan.



#### Test Parameters

- A test consists of three sets of five to seven piston “tightenings.” In a tightening, the torque decrease is measured as the spark plug gasket temperature increases from 200°C to 300°C.
- The first and third sets are conducted using Jatco-1 reference lubricant.
- The second set is conducted using the candidate lubricant.

Each set is preceded by a 30-minute preliminary operation period at the following test conditions:

- The cooling fan is then stopped. During the tightening, the torque and spark plug gasket temperature are monitored.
- When the spark plug gasket temperature reaches 300°C, the cooling fan is restored and the engine is allowed to cool while running.
- When the spark plug gasket temperature is 160°C, the engine is allowed to stabilize for five minutes before starting the next tightening. During this time, the exhaust gas CO<sub>2</sub> is checked.
- This operational cycle continues until three sets of five to seven tightenings per set are obtained.

#### Test Parts Evaluation

- None.

#### Used Lubricant Analysis

- None.

#### Pass/Fail Criteria

- The minimum lubricity index is 95 for all grades (FB, EGB, FC, EGC, FD, EGD).
- Lubricants in each grade correspond to the following two-stroke cycle lubricants:
  - The FB and EGB grades correspond to lubricants that have high performance in lubricity, but are non-low-smoke type.
  - The FC and EGC grades correspond to lubricants typical of low-smoke type lubricants in the Japanese market.
  - The FD and EGD grades correspond to lubricants that have greater detergency performance as identified in International Standard 13738.

Parameter	Value
Engine speed, rpm	4000
Spark plug gasket temp, °C	160
Torque, Nm	WOT
Exhaust gas CO concentration, %	6
Fuel/lubricant ratio	50:1

**We welcome your inquiries. For additional information, please contact:**

**Patrick Lang**

Manager

210.522.2820


*patrick.lang@swri.org*

Fuels and Lubricants Research Division

Southwest Research Institute

6220 Culebra Road

San Antonio, Texas 78238-5166



**[lubricanttesting.swri.org](https://lubricanttesting.swri.org)**

Southwest Research Institute® is a premier independent, nonprofit research and development organization. With ten technical divisions, we offer multidisciplinary services leveraging advanced science and applied technologies. Since 1947, we have provided solutions for some of the world's most challenging scientific and engineering problems.



Benefiting government, industry and the public through innovative science and technology

210.522.2122

[ask@swri.org](mailto:ask@swri.org)

Like. Share. Follow. Listen.



**swri.org**

©2025 Southwest Research Institute.  
All rights reserved.